

KOELKAST ADVANCE K 70-3 L DR

Product Serie: Advance

Artikelnummer: 121701010

Hoshizaki ADVANCE is a series of durable refrigeration and freezer cabinets, exceeding the requirements of demanding commercial kitchen environments.

The Advance K 70-3 L DR is a Refrigerator with a net internal volume of 415 liters. The outside dimensions are 654 x 830 x 1980-2030 mm.

DURABLE MATERIALS

The interior and exterior are made of stainless steel, the best material for humid locations. ADVANCE cabinets are designed to withstand the demanding conditions of large kitchen operations.

MAXIMUM STORAGE SPACE

With shelves all the way from the top to the bottom of the cabinet, the inside space can be efficiently utilized for maximum produce storage.

HYGIENE AND FOOD SAFETY

Thanks to the rounded corners and seamless surfaces, frequented cleaning routines become a quick and simple task. The practical anti-tilting shelves prevent spillage. The cabinet has a rounded base and comes with removable gaskets for easy wiping.

MONO-BLOCK DESIGN

The ADVANCE refrigeration system uses a mono-block construction. This brings two important advantages. As the evaporator is positioned on top of the cabinet, valuable space inside the cabinet can be used for storage. Additionally, it is removable for easier maintenance and repair.

UNIFORM KITCHEN DESIGN

The exterior of all ADVANCE cabinets features a uniform design that fits seamlessly into your Hoshizaki kitchen concept.

TEMPERATURE STABILITY

The intelligent air distribution system allows high performance, ensuring temperature stability despite frequent door openings and during defrosting.



SPECIFICATIES

Productnaam	Koelkast	Standaard energie Efficiëntieklasse	ISO 22041-2019
Temperatuurbereik	0/+10°C	Energie Efficiëntieklasse	C
Inhoud, bruto (liter)	600	Energie Efficiëntie Index EEI	42,41
Netto bruikbaar volume (liter)	415	Geluidsniveau dB(A)	50
Uitwendig	RvS AISI 304	Klimaatklasse	5
Inwendig	RvS AISI 304	Opties	Legs/castor, grey/stainless shelves, right or left hand hinged door
Afmetingen B x D x H (mm)	654 x 830 x 1980-2030	Poten / Wielset	H = 130/180 mm (L)
Gewicht, verpakt (kg)	122	Koelmiddel (kg)	0,058
Isolatie (mm)	60 (polyurethaan)	CO2 Equivalent (kg)	0,17
Koelmiddel	R290	GN – Afmetingen rooster	2/1 GN diep
GWP	3	Maximaal aantal roosters	22
Koelcapaciteit bij -10°C (Watt)	361	Aantal roosters	4
Aansluiting	230V, 50 Hz	Uitgerust met	Rechtsdraaiende omkeerbare deur met slot, automatische deursluiting, 4 grijze roosters, LED-verlichting
Aansluitwaarde (Watt)	140	Deur type	Geïsoleerde deur
Energie verbruik (kWh/Jaar)	548		